



AQT-275

PRODUCT SPECIFICATIONS

AQT-275 Timer/Meter Valves

Aquatrol 275 Timer/Meter Mechanical Valves offer a flanged body design for convenient maintenance and are made of solid lead-free brass for superior strength and durability. The AQT-275 also offers a NHWB piston and is 5 cycle adjustable.

FEATURES

- Lead free brass body
- Adjustable 5 cycle control
- Residential / light commercial applications
- Backwash capacity for tanks up to 21" (Filters) and 24" (Softeners) diameter
- 1" Control valve
- NHWB option available
- Time clock: 7 and 12 days - Manual or Meter
- Meter: delayed or immediate regeneration



Models:	
AQT-275ST:	Softener Timer
AQT-275SM:	Softener Meter
AQT-275ST-NX	Electronic Softener Timer
AQT-275SM-NX	Electronic Softener Meter
AQT-275FT:	Filter Timer
AQT-275FM:	Filter Meter
AQT-275FT-NX	Electronic Filter Timer
AQT-275FM-NX	Electronic Filter Meter

Flow Rate 50 psi (3.5 bar) Valve Alone:	
Continuous 15 psi (1 bar) Drop:	26 gpm (98 lpm)
Peak 25 psi (1.7 bar) Drop:	33 gpm (125 lpm)
Max Backwash 25 psi (1.7 bar) Drop:	25 gpm (95 lpm)
CV 1 psi (0.07 bar) Drop:	6.8

Regeneration/Backwash:	
Downflow/Upflow:	Downflow or Upflow
Cycles:	5
Adjustable Cycles:	Mechanical, All
Time Available:	164 Minutes

Meter:	
Accuracy:	0.7 - 40 gpm (2.7 - 151 lpm) ± 5%
Capacity Range:	Standard: 310 - 5,270 gal (1.2 - 20m ³) Extended: 1,550 - 26,350 gal (6 - 100m ³)

Valve Specifications:	
Inlet/Outlet:	1" NPT
Mounting Base:	2-1/2" - 8 NPSM
Distributor Pilot:	1.05" OD
Drain Line:	3/4"
Brine Line:	3/8" or 1/2"
Height:	7" (198 mm)
Weight (Valve Gross):	Timer 13.2 lb (6 kg) Meter 17.2 lb (7.8 kg)

Additional Information:	
Electrical Rating:	220V, 110V, 24V - 50Hz, 60Hz
Max. VA	74 VA
Water Pressure:	Hydrostatic: 300 psi (20 bar) Working: 20 - 120 psi (1.4 bar - 8 bar)
Temperature:	34 - 110° F (1 - 43° C)



AQUATROL | P.O. Box 2235 Chino Hills, CA 91709 • USA

Distributed by: