


# Pretreat Plus® Select

Antiscalant/Dispersant/Antifoulant



**Pretreat Plus® Select** is a classic antiscalant specifically formulated for feedwaters with lower levels of scale-forming minerals, such as seawater, to be cost effective. It is effective over a wide range of concentrations, and does not flocculate dissolved polymers such as residual coagulants or iron- or aluminum-rich silica. Use of this product is recommended for reducing the operating and capital costs of reverse osmosis (RO) and nanofiltration (NF) systems.

## Features

- Controls inorganic scale over a large concentration range.
- Decreases precipitation of aluminum, iron, and heavy metal salts.
- Compatible with RO, NF, and UF membranes from all major manufacturers.
- Liquid formulation is convenient and easy to use.
- Certified under NSF/ANSI Standard 60 for drinking water production.



### Dosage

In the typical dosage range of 1-10 mg/L (neat), control of a wide range of inorganic scales at up to 100x saturation values or higher is possible. By monitoring the concentrate stream and trend charts using iWater-PRO™, optimal dosage can be achieved for the control of scales.



### Specs

Appearance: Clear, Colorless Liquid	Product pH (neat): ≤ 2.5
Specific Gravity: 1.01 ± 0.01	Feedwater pH: 5.0-10.0

## Application

Pretreat Plus® Select should be injected into the feed stream prior to the static mixer and cartridge filter. Effective pH range is 5.0-10. If frozen, may be thawed and mixed before use.



## Packaging

5 gal (20kg), 55 gal (220kg),  
220 gal (969 kg), 275 gal (1211 kg)  
Bulk

